

Model			GWH18ACDXF-K6DNA1A GWH18ACDXF-K6DNA3A	GWH18ACDXF-K6DNA1A
Product Code			CB497016900 CB343004500	CB497016901/CB497016902/ CB497016903/CB497016904
Power Supply	Rated Voltage	V~	220-240	220-240
	Rated Frequency	Hz	50	50
	Phases		1	1
Power Supply Mode			Outdoor	Outdoor
Cooling Capacity	W		5300	5300
Heating Capacity	W		5600	5600
Cooling Power Input	W		1413	1413
Heating Power Input	W		1333	1333
Cooling Current Input	A		6.5	6.5
Heating Current Input	A		6.2	6.2
Rated Input	W		2500	2500
Rated Cooling Current	A		11.5	11.5
Rated Heating Current	A		12.5	12.5
Air Flow Volume	m ³ /h		850/750/680/610/570/520/460	850/750/680/610/570/520/460
Dehumidifying Volume	L/h		1.9	1.9
EER	W/W		3.75	3.75
COP	W/W		4.20	4.20
SEER	W/W		7.6	7.6
SCOP(Average/WarmerColder)	W/W		4.3/5.8/3.5	4.3/5.8/3.5
Application Area	m ²		23-34	23-34
Indoor Unit	Model		GWH18ACDXF-K6DNA1A/I GWH18ACDXF-K6DNA3A/I	GWH18ACDXF-K6DNA1A/I
	Product Code		CB497N16900 CB343N04500	CB497N16900/CB497N16902/ CB497N16903/CB497N16904
	Fan Type		Cross-flow	Cross-flow
	Fan Diameter Length(DXL)	mm	Φ106×706	Φ106×706
	Cooling Speed	r/min	1230/1170/1100/1020/960/880/800/550	1230/1170/1100/1020/960/880/800/550
	Heating Speed	r/min	1400/1270/1200/1130/1050/980/900	1400/1270/1200/1130/1050/980/900
	Fan Motor Power Output	W	45	45
	Fan Motor RLA	A	0.24	0.24
	Fan Motor Capacitor	μF	/	/
	Evaporator Form		Aluminum Fin-copper Tube	Aluminum Fin-copper Tube
	Evaporator Pipe Diameter	mm	Φ7	Φ7
	Evaporator Row-fin Gap	mm	2-1.4	2-1.4
	Evaporator Coil Length (LXDXW)	mm	715×25.4×304.8	715×25.4×304.8
	Swing Motor Model		MP35CJ/MP24HF	MP35CJ/MP24HF
	Swing Motor Power Output	W	2.5/1.5	2.5/1.5
	Fuse Current	A	3.15	3.15
	Sound Pressure Level	dB (A)	Cooling:43/41/39/37/35/32/31/21 Heating:47/45/42/40/38/36/33	Cooling:43/41/39/37/35/32/31/21 Heating:47/45/42/40/38/36/33
	Sound Power Level	dB (A)	Cooling:60/57/55/54/52/50/46/34 Heating:60/58/57/56/54/52/48	Cooling:60/57/55/54/52/50/46/34 Heating:60/58/57/56/54/52/48
	Dimension (WXHXD)	mm	1013X307X221	1013X307X221
	Dimension of Carton Box (LXWXH)	mm	1055X366X287	1055X366X287
Dimension of Package (LXWXH)	mm	1060X374X297	1060X374X297	
Net Weight	kg	13	13	
Gross Weight	kg	15.5	15.5	