

Model			GWH12AGC-K6DNA1A	GWH24AGD-K6DNA1A
Product Code			CB385002400	CB385001500
Power Supply	Rated Voltage	V~	220-240	220-240
	Rated Frequency	Hz	50	50
	Phases		1	1
Power Supply Mode			Outdoor	Outdoor
Cooling Capacity		W	3200	6200
Heating Capacity		W	3400	6500
Cooling Power Input		W	933	1631
Heating Power Input		W	872	1645
Cooling Power Current		A	4.15	7.5
Heating Power Current		A	3.86	7.6
Rated Input		W	1500	2200
Rated Current		A	6	9.3
Rated Heating Current		A	7.5	9.7
Air Flow Volume(SS/H/MH/M/ML/L/SL)		m ³ /h	680/620/560/490/450/420/390	1050/950/800/750/700/650/600
Dehumidifying Volume		L/h	1.4	1.8
EER		W/W	3.43	3.80
COP		W/W	3.90	3.95
SEER		W/W	6.5	/
SCOP(Average/Warmer/Colder)			4.1/5.1/-	4.3/5.3/-
HSPF			/	/
Application Area		m ²	15-22	23-34
Indoor Unit	Indoor Unit Model		GWH12AGC-K6DNA1A/I	GWH24AGD-K6DNA1A/I
	Indoor Unit Product Code		CB385N02400	CB385N01500
	Fan Type		Cross-flow	Cross-flow
	Diameter Length(DXL)	mm	Φ98X630	Φ106X739
	Fan Motor Cooling Speed(SS/H/MH/M/ML/L/SL)	r/min	1300/1150/1100/1000 /950/850/750	1370/1200/1100/1000/920/850/750
	Fan Motor Heating Speed(SS/H/MH/M/ML/L/SL)	r/min	1250/1100/1050/1000/950/850/800	1370/1200/1120/1050/980/900/850
	Output of Fan Motor	W	20	50
	Fan Motor RLA	A	0.30	0.24
	Fan Motor Capacitor	μF	1.5	/
	Input of Heater	W	/	/
	Evaporator Form		Aluminum Fin-copper Tube	Aluminum Fin-copper Tube
	Pipe Diameter	mm	Φ5	Φ7
	Row-fin Gap	mm	2-1.4	2-1.4
	Coil Length (LXDXW)	mm	634X22.8X304.8	745X22.8X342.9
	Swing Motor Model		MP24BA/MP24AK/MP24HF	MP24BA/MP24AK/MP24HF
	Output of Swing Motor	W	1.5/1.5/1.5	1.5/1.5/1.5
	Fuse	A	3.15	3.15
	Sound Pressure Level(SS/H/MH/M/ML/L/SL)	dB (A)	Cooling:41/37/35/33/31/27/22 Heating:41/36/34/32/30/27/25	Cooling:46/42/40/38/36/32/25 Heating:49/44/42/40/36/32/29
	Sound Power Level(SS/H/MH/M/ML/L/SL)	dB (A)	Cooling:57/50/48/46/43/39/36 Heating:55/49/47/45/43/40/37	Cooling:63/59/57/55/53/49/42 Heating:63/58/56/54/50/46/43
	Dimension (WXHXD)	mm	825X293X196	982X311X221
Dimension of Carton Box (LXWXH)	mm	870X349X257	1039X377X287	
Dimension of Package (LXWXH)	mm	875X365X268	1044X385X297	
Net Weight	kg	10	13.5	
Gross Weight	kg	12	16	

