

Model	Indoor Unit		GUD35P1/A-S GUD35PS1/A-S	GUD50P1/A-S GUD50PS1/A-S	GUD71PH1/A-S GUD71PHS1/A-S	GUD85PH1/A-S GUD85PHS1/A-S
	Outdoor Unit		GUD35W1/NhA-S	GUD50W1/NhA-S	GUD71W1/NhA-S	GUD85W1/NhA-S
Connection Pipe	Liquid Pipe	in.	Φ1/4	Φ1/4	Φ3/8	Φ3/8
	Gas Pipe	in.	Φ3/8	Φ1/2	Φ5/8	Φ5/8
Refrigerant Pipe	Standard Length	m	5	5	5	5
	Max. Length	m	30	30	30	30
	Max. Height	m	15	20	20	25
Dimensions (W×D×H)	Outline	mm	675×285×553	745×300×555	889×340×660	889×340×660
	Package	mm	794×376×605	872×398×609	1032×456×730	1032×456×730
Weight	Net/Gross	kg	24.5/27.0	30.5/33.0	41.5/45.0	46.0/50.0

Model	Indoor Unit		GUD100PH1/A-S GUD100PHS1/A-S	GUD125PH1/A-S GUD125PHS1/A-S	GUD140PH1/A-S GUD140PHS1/A-S
	Outdoor Unit		GUD100W1/NhA-S	GUD125W1/NhA-S	GUD140W1/NhA-S
Rated Capacity	Cooling	kW	10.50	12.10	13.40
	Heating	kW	11.50	13.50	15.50
Input Power	Cooling	kW	3.00	3.58	4.50
	Heating	kW	2.80	3.70	4.50
EER/ COP		W/W	3.50/4.10	3.38/3.65	2.98/3.44
SEER/SCOP		—	6.40/4.20	6.10/4.10	6.10/4.00
Energy Class (Cooling /Heating)		—	A++/A+	A++/A+	A++/A+
Indoor Unit			GUD100PH1/A-S GUD100PHS1/A-S	GUD125PH1/A-S GUD125PHS1/A-S	GUD140PH1/A-S GUD140PHS1/A-S
Power Supply			220-240V ~50/60Hz		
Heat Exchanger		—	Inner Groove Copper Tube-Aluminum Fin		
Fan Motor	Type	—	Centrifugal Fan		
	Air Volume (SH/H/M/L)	m³/h	1700/1600/1400/1200	2000/1800/1600/1400	2300/2100/1800/1500
	External Static Pressure Standard	Pa	37	50	50
Filter		—	PP	PP	PP
Sound Pressure Level(SH/H/M/L)		dB(A)	39/38/37/36	43/42/41/40	43/42/40/38
Connection Pipe	Liquid Pipe	in.	Φ3/8	Φ3/8	Φ3/8
	Gas Pipe	in.	Φ5/8	Φ5/8	Φ5/8
	Water Pipe	mm	Φ26×2.5	Φ26×2.5	Φ26×2.5
Dimensions (W×D×H)	Outline	mm	1340×655×260	1340×655×260	1400×700×300
	Package	mm	1568×770×323	1568×770×323	1601×813×365
Weight without Drain Pump	Net/Gross	kg	42.0/48.0	42.0/48.0	51.0/57.0
Weight with Drain Pump		kg	43.0/49.0	43.0/49.0	52.0/58.0
Outdoor Unit			GUD100W1/NhA-S	GUD125W1/NhA-S	GUD140W1/NhA-S
Heat Exchanger			Inner Groove Copper Tube-Aluminum Fin		
Power Supply			220-240V ~50/60Hz		

U-MATCH SERIES AIR CONDITIONERS

Model	Indoor Unit		GUD100PH1/A-S GUD100PHS1/A-S	GUD125PH1/A-S GUD125PHS1/A-S	GUD140PH1/A-S GUD140PHS1/A-S	
	Outdoor Unit		GUD100W1/NhA-S	GUD125W1/NhA-S	GUD140W1/NhA-S	
Compressor	Model		QXFS-D280zX070	QXFS-D280zX070	QXFS- D280zX070B	
	Type		Rotary	Rotary	Rotary	
Fan Motor	Type	—	Axial Fan	Axial Fan	Axial Fan	
	Air Volume	m ³ /h	4800	5200	5200	
Sound Pressure Level		dB(A)	57	58	59	
Refrigerant	Type		R32	R32	R32	
	Weight	kg	2.1	2.25	2.80	
	Throttling Method		Electronic Expansion Valve			
Connection Pipe	Liquid Pipe	in.	Φ3/8	Φ3/8	Φ3/8	
	Gas Pipe	in.	Φ5/8	Φ5/8	Φ5/8	
Refrigerant Pipe	Standard Length	m	5	5	7.5	
	Max. Length	m	75	75	75	
	Max. Height	m	30	30	30	
Dimensions (W×D×H)	Outline	mm	940×370×820	940×370×820	940×370×820	
	Package	mm	1093×497×885	1093×497×885	1093×497×885	
Weight	Net/Gross		kg	65.0/72.0	66.0/73.0	73.0/80.0

Model	Indoor Unit		GUD100PH1/A-S GUD100PHS1/A-S	GUD125PH1/A-S GUD125PHS1/A-S	GUD140PH1/A-S GUD140PHS1/A-S	GUD160PH1/A-S GUD160PHS1/A-S	
	Outdoor Unit		GUD100W1/NhA-X	GUD125W1/NhA-X	GUD140W1/NhA-X	GUD160W1/NhA-X	
Rated Capacity	Cooling	kW	10.50	12.10	13.40	16.00	
	Heating	kW	11.50	13.50	15.50	17.00	
Input Power	Cooling	kW	3.00	3.58	4.50	5.40	
	Heating	kW	2.80	3.70	4.50	4.70	
EER/ COP		W/W	3.50/4.10	3.38/3.65	2.98/3.44	2.96/3.62	
SEER/SCOP		—	6.40/4.20	6.10/4.10	6.10/4.00	6.10/4.00	
Energy Class (Cooling /Heating)		—	A++/A+	A++/A+	A++/A+	A++/A+	
Indoor Unit			GUD100PH1/A-S GUD100PHS1/A-S	GUD125PH1/A-S GUD125PHS1/A-S	GUD140PH1/A-S GUD140PHS1/A-S	GUD160PH1/A-S GUD160PHS1/A-S	
Power Supply			220-240V ~50/60Hz				
Heat Exchanger			— Inner Groove Copper Tube-Aluminum Fin				
Fan Motor	Type	—	Centrifugal Fan				
	Air Volume (SH/H/M/L)	m ³ /h	1700/1600/ 1400/1200	2000/1800/ 1600/1400	2300/2100/ 1800/1500	2600/2300/ 2000/1700	
	External Static Pressure Standard	Pa	37	50	50	50	
Filter			— PP PP PP PP				
Sound Pressure Level (SH/H/M/L)			dB(A)	39/38/37/36	43/42/41/40	43/42/40/38	46/44/42/40